



## JH 10 G plus EX - hydraulic jack without integrated pump unit

Load capacity: 10 t

Stroke: 150 mm

Art.-Nr. 11 610 106-G

### Advantages of jacks – Series JH G plus EX

- Integrated spring return retracts piston automatically on JH 15 up to JH 30 G plus EX.
- Slide shoe design inside the guiding track prevents twisting of the piston inside the lifting cylinder. This guarantees better force distribution, less friction and reduced wear compared to conventional jacks.
- Reduced maintenance costs due to removable stroke unit and easy to change slide shoes.
- Extremely lightweight with high performance due to the use of highquality material and innovative design.
- Continuous adjustment to the load due to swiveling safety toe. Secure stableness in every situation even in lifted position.

Here you find an [application video](#).

## Technical data

Title	Unit	Data
Load capacity on top plate	kg	10000
Stroke	mm	150
Minimum lift toe height	mm	15
Maximum lift toe height	mm	180
Lift toe adjustment	mm	5 x 41
Top plate height	mm	275
Toe width front	mm	60
Toe depth	mm	55
Length feet in front	mm	270
Length feet on side	mm	251

Title	Unit	Data
Width	mm	247
Height	mm	308
Cylinder volume	L	0,3
Weight	kg	29