



JH 20 G plus - hydraulic jack with integrated pump unit

Load capacity: 20 t
Stroke: 190 mm

Art.-Nr. 01 200 102-G

Advantages of jacks – Series JH G plus

- Slide shoe design inside the guiding track prevents twisting of the piston inside the lifting cylinder. This guarantees better force distribution, less friction and reduced wear compared to conventional jacks.
- Reduced maintenance costs due to easy change slide shoes and removable pump unit.
- Extremely lightweight with high performance due to the use of highquality material and innovative design.
- Continuous adjustment to the load due to swiveling safety toe. Secure stableness in every situation even in lifted position.
- JH 15 / JH 20 G plus serial outfitted with fast stroke. Also available with spring return.
- Die-forged steel toe provides impact resistance.

Here you find an [application video](#).

Technical data

Title	Unit	Data
Load capacity on top plate	kg	20000
Stroke	mm	190
Minimum lift toe height	mm	20
Maximum lift toe height	mm	225
Lift toe adjustment	mm	5 x 51
Top plate height	mm	340
Toe width front	mm	80
Toe depth	mm	64
Length feet in front	mm	425

Title	Unit	Data
Length feet on side	mm	405
Width	mm	322
Height	mm	340
Cylinder volume	L	0,73
Weight	kg	60