



JH 30 G plus EX - hydraulic jack without integrated pump unit

Load capacity: 30 t
Stroke: 200 mm

Art.-Nr. 11 630 106-G

Advantages of jacks – Series JH G plus EX

- Integrated spring return retracts piston automatically on JH 15 up to JH 30 G plus EX.
- Slide shoe design inside the guiding track prevents twisting of the piston inside the lifting cylinder. This guarantees better force distribution, less friction and reduced wear compared to conventional jacks.
- Reduced maintenance costs due to removable stroke unit and easy to change slide shoes.
- Extremely lightweight with high performance due to the use of highquality material and innovative design.
- Continuous adjustment to the load due to swiveling safety toe. Secure stableness in every situation even in lifted position.

Here you find an [application video](#).

Technical data

| Title | Unit | Data |
|----------------------------|------|--------|
| Load capacity on top plate | kg | 30000 |
| Stroke | mm | 200 |
| Minimum lift toe height | mm | 20 |
| Maximum lift toe height | mm | 304 |
| Lift toe adjustment | mm | 5 x 71 |
| Top plate height | mm | 420 |
| Toe width front | mm | 80 |
| Toe depth | mm | 64 |
| Length feet in front | mm | 380 |

| Title | Unit | Data |
|---------------------|------|------|
| Length feet on side | mm | 370 |
| Width | mm | 375 |
| Height | mm | 420 |
| Cylinder volume | L | 1,27 |
| Weight | kg | 95 |