



JH 6 G plus - hydraulic jack with integrated pump unit

Load capacity: 6 t

Stroke: 140 mm

With side handles and no standard handle

Art.-Nr. 01 060 102-G-G

Advantages of jacks – Series JH G plus

- Slide shoe design inside the guiding track prevents twisting of the piston inside the lifting cylinder. This guarantees better force distribution, less friction and reduced wear compared to conventional jacks.
- Reduced maintenance costs due to easy change slide shoes and removable pump unit.
- Extremely lightweight with high performance due to the use of highquality material and innovative design.
- Continuous adjustment to the load due to swiveling safety toe. Secure stableness in every situation even in lifted position.
- JH 15 / JH 20 G plus serial outfitted with fast stroke.
- Die-forged steel toe provides impact resistance.
- With additional side handles and no standard handle

Here you find an [application video](#).

Technical data

Title	Unit	Data
Load capacity on top plate	kg	6000
Stroke	mm	140
Minimum lift toe height	mm	12
Maximum lift toe height	mm	157
Lift toe adjustment	mm	6 x 29
Top plate height	mm	245
Toe width front	mm	50

Title	Unit	Data
Toe depth	mm	50
Length feet in front	mm	326
Length feet on side	mm	311
Width	mm	233
Height	mm	280
Cylinder volume	L	0,18
Weight	kg	22