

JHS 10 - hydraulic jack without pump and hose
Load capacity: 10 t
Stroke: 260 mm

Art.-Nr. 01 020 101-O

Advantages of jacks – Series JHS

- 180° revolving housing, this allows the jack to be placed with long or with short feet to the load, if there is no space under that.
- Extra-large lift height: JHS 10 with lift toe 260 mm, with top plate maximum 610 mm.
- Large load capacity – up to 20 metric tons in set - with low net weight, therefore perfect for use on site or on the way by frequent changes of location.
- Can also be used horizontally for pressing.
- Safe: because of the use of a separate pump and hoses, more safety distance to the load.

Here you find an application video.

Technical data

Title	Unit	Data
Load capacity	kg	10000
Minimum lift toe height	mm	20
Maximum lift toe hight	mm	260
Top plate height	mm	370
Maximum top plate height	mm	610
Toe width front	mm	60
Toe depth	mm	55
Diameter top plate	mm	80
Length toe supported without handle	mm	205
Length toe exposed without handle	mm	260

Biegelwiesenstraße 5-7
D-71334 Waiblingen
info@jung-hebetechnik.de
☎ + 49 (0) 71 51 / 3 03 93 - 0
+ 49 (0) 71 51 / 3 03 93 -19

Title	Unit	Data
Width	mm	200
Cylinder volume	L	0,47
Weight	kg	19

Biegelwiesenstraße 5-7
D-71334 Waiblingen
info@jung-hebetechnik.de
☎ + 49 (0) 71 51 / 3 03 93 - 0
+ 49 (0) 71 51 / 3 03 93 -19