



JKB 6 Set with JUWAmid

Load capacity: 2 x 6 t

Height: 110 mm

Art.-Nr. 14 061 085-D

Advantages of revolving transport trolleys

- Optional connecting bars can be fixed without tools by clamping down on adapter.
- High load capacity at low weight.
- Bearing supported swiveling castors allow 360° maneuverability.
- Mix and match revolving trolleys with transport trolleys: With an installation height of only 110 mm*, the rotating transport trolley JKB 6 is compatible with all steering and transport undercarriages of the K series.
- All products are also available in a set of two with price advantage.
- Unrivalled: The double roller system reduces rolling and turning resistance to a minimum.
- Using the slots in the platform, the trolleys JKB 4 - 8 can be affixed to the load with standard tiedown belts.
- In addition, all the rotational trolleys have a platform center hole to allow attachment to the load.
- For choosing the adequate revolving trolley we recommend a load of two-third of the maximum capacity. This will be the most advantageous compromise between payload, ergonomics and handling of the devices.
- Pulling handle and connecting bars available as accessories.
- Inspected according to technical regulation ANSI ? ASME (USA)

Here you find an [application video](#).

*) Due to technical changes, there may be tolerances of up to + 4.5 mm in the installation height since 2014.

Technical data

Title	Unit	Data
Consist of		2 x JKB 6 K
Load capacity	kg	2 x 6000

Title	Unit	Data
Number of castors	pcs.	2 x 16
Castor dimensions Ø x Fitting length	mm	85 x 43
Height	mm	110
Supporting surface of turntable Ø	mm	250
Cassette dimensions	mm	675 x 525
Weight JUWAmid	kg	89