

JLA-p 15 ? 30 G Load capacity: 15 t Height: 180 mm

Art.-Nr. 22 150 140-V

Advantages of air-powered transport trolleys

- Quick set up. Connect air supply hose and go.
- Spare a towing vehicle.
- Low maintenance propulsion system.
- All hoses are detachable for compact and easy transport.
- 360° maneuverable.
- No need to charge any batteries.
- Ecofriendly, uses only compressed air.
- Requires standard shop air connection with 8 bar (116 psi) and air volume of 1500 L? min (25 L?s) or (53 SCFM).
- Infinitely variable speed and direction.
- Compatible with G-series transport trolleys (page 32-33).
- Model JLA-p 15 ? 30 G includes the trolley and remote control unit.
- Two air motors are independently controllable by two joysticks.
- Maneuverability: Forward, reverse, in place turning.
- Higher capacities available on request.

Technical data

Title	Unit	Data
Load capacity	kg	15000
Pulling capactiy	kg	30000
Number of castors	pcs.	16
Castor dimensions Ø x Fitting	mm	140 x 120 / 140 x 59
length		
Height	mm	180
		180 215
Height		



Title	Unit	Data
Air consumption	L pro sec.	25
Required air pressure	bar	8



+ 49 (0) 71 51 /3 03 93 - 0 + 49 (0) 71 51 /3 03 93 -19