

JLF 3,5

Load capacity: 3,5 t Height: 150 mm

Art.-Nr. 16 035 085-D

Advantages of multi-purpose transport trolleys

- Combined leading swiveling castors with trailing rigid castors. Swiveling leadcastors make steering easier by up to 80 %.
- Ergonomic: reduces handling effort for user.
- Better directional stability on long straight-line paths with trailing rigid castors.
- Each trolley can be used for either steerable or straight-line movements.
- Extreme maneuverable with thrust bearing supported, anti-slip turntable.
- Trolleys can be used as steerable, adjustable or tandem trolley.
- Ideal for transporting loads on slalom paths including 90° true-to-course straightline, turning and sideways maneuvering.
- Floor protective, non-marking coating.
- Low profile. Low weight.
- Included in set is an additional pulling handle for steering of rear-trailing trolleys for tighter turning radius.
- Inspected according to technical regulation ANSI ? ASME (USA)

Registered design EU No. 002267487- 001

Here you find an application video.

Technical data

Title	Unit	Data
Load capacity	kg	3500
Number of castors? twin castors	pcs.	4/2
Castor dimensions Ø x Fitting	mm	85 x 43
length		
Height	mm	150
Supporting surface of turntable Ø	mm	150
Length	mm	410 x 420



Title	Unit	Data
Weight JUWAthan®plus	kg	25



+ 49 (0) 71 51 /3 03 93 - 0 + 49 (0) 71 51 /3 03 93 -19