



JLF 5

Load capacity: 5 t

Height: 150 mm

Art.-Nr. 16 050 085-D

Advantages of multi-purpose transport trolleys

- Combined leading swiveling castors with trailing rigid castors. Swiveling lead castors make steering easier by up to 80 %.
- Ergonomic: reduces handling effort for user.
- Better directional stability on long straight-line paths with trailing rigid castors.
- Each trolley can be used for either steerable or straight-line movements.
- Extreme maneuverable with thrust bearing supported, anti-slip turntable.
- Trolleys can be used as steerable, adjustable or tandem trolley.
- Ideal for transporting loads on slalom paths including 90° true-to-course straight line, turning and sideways maneuvering.
- Floor protective, non-marking coating.
- Low profile. Low weight.
- Included in set is an additional pulling handle for steering of rear-trailing trolleys for tighter turning radius.
- Inspected according to technical regulation ANSI ? ASME (USA)

Registered design EU No. 002267487- 001

Here you find an [application video](#).

Technical data

Title	Unit	Data
Load capacity	kg	5000
Number of castors? twin castors	pcs.	4 / 4
Castor dimensions Ø x Fitting length	mm	85 x 43
Height	mm	150
Supporting surface of turntable Ø	mm	150
Length	mm	410 x 420

Title	Unit	Data
Weight JUWATHAN®plus	kg	28