

JLF Set 12

Load capacity: $1 \times 5 t + 2 \times 3,5 t$

Height: 150 mm

Art.-Nr. 16 120 085-D

Advantages of multi-purpose transport trolleys

- Combined leading swiveling castors with trailing rigid castors. Swiveling lead castors make steering easier by up to 80 %.
- Ergonomic: reduces handling effort for user.
- Better directional stability on long straight-line paths with trailing rigid castors.
- Each trolley can be used for either steerable or straight-line movements.
- Extreme maneuverable with thrust bearing supported, anti-slip turntable.
- Trolleys can be used as steerable, adjustable or tandem trolley.
- Ideal for transporting loads on slalom paths including 90° true-to-course straight line,turning and sideways maneuvering.
- Floor protective, non-marking coating.
- Low profile. Low weight.
- Included in set is an additional pulling handle for steering of rear-trailing trolleys for tighter turning radius.

Here you find an application video.

Technical data

Title	Unit	Data
Load capacity	kg	1 x 5000 + 2 x 3500
Number of castors? twin castors	pcs.	3 x 4 / 2 x 2 + 1 x 4
Castor dimensions Ø x Fitting	mm	85 x 43
length		
Height	mm	150
Supporting surface of turntable Ø	mm	150
Length	mm	410 x 420
Handlebar with pulling eye	mm	1210 x 300 x 40
Connecting bar Ø x L	mm	20 x 1200



Title	Unit	Data
Weight JUWAthan®plus	kg	89



+ 49 (0) 71 51 /3 03 93 - 0 + 49 (0) 71 51 /3 03 93 -19