

Steerable trolley JLB 40 H Professional - NEW

Strength and reliability combined: The JLB 40 H transport trolley from JUNG handles loads up to 40 t with a compact installation height of just 230 mm.

Product number 09 401 206-H

Weight 294kg



Product description

Features of the JUNG Transport trolleys JLB 40 H Professional

- Despite their very high load capacity, these transport trolleys remain compact and lightweight.
- The redesigned steering unit features fewer rollers, allowing for a more compact design without compromising load capacity – made possible by advanced roller technology.
- The new, more compact construction and reduced number of rollers result in a noticeable weight reduction.
- By halving the roller width and doubling the number of rollers, steering movements are significantly improved and friction during cornering is greatly reduced.
- The mechanical pendulum mounting of the cassettes and axles ensures even load distribution across the rollers and the floor surface – eliminating the need for complex and failure-prone hydraulic compensation systems.
- All transport trolleys are delivered fully assembled and ready for immediate use. The steering unit is supplied with a ball-bearing turntable and drawbar; the drawbar is equipped with a towing eye.

JUNG transport trolleys are fitted with ball-bearing rollers for smooth and effortless movement. The rollers come standard with a low-wear tread.

Product properties

Handlebar with pulling eye (mm)	1 600
Load capacity (suitable)	61 - 200 t
Weight JUWAthan® (kg)	294
Supporting surface of turnable Ø (mm)	250
Height (mm)	230
Number of castors (Pieces)	12
Castor dimensions (Ø x l mm)	200 x 85
Load capacity (t)	40
Dimensions steerable (mm)	650 x 1 060

More images

