

# Steerable trolley JLB 60 H Professional - NEW

Engineered for power and stability: JUNG JLB 60 H Professional - NEW transport trolley can lift loads of up to 60 t with an installation height of 230 mm.

**Product number** 09 601 206-H

**Weight** 385kg



## Product description

Features of the JUNG Transport trolleys JLB 60 H Professional

- Despite their high load-bearing capacity, the transport trolleys feature a compact and lightweight design.
- The newly developed steering unit with a reduced number of rollers allows for a space-saving construction while maintaining the same load capacity – made possible by state-of-the-art roller technology.
- The more compact design and reduced number of rollers result in a significant weight reduction.
- By halving the roller width and doubling the number of rollers, steering is noticeably improved and frictional forces during cornering are significantly reduced.
- The mechanical pendulum suspension of the cassettes or axles ensures uniform load distribution across the rollers and the floor surface – eliminating the need for a complex and failure-prone hydraulic leveling system.
- All transport trolleys are delivered pre-assembled and are ready for immediate use.
- The steering unit is equipped with a ball-bearing turntable and a tow bar with an integrated towing eye.

JUNG transport trolleys are fitted with ball-bearing rollers for smooth and effortless movement. The rollers come standard with a low-wear tread.

## Product properties

<b>Handlebar with pulling eye (mm)</b>	1 600
<b>Load capacity (suitable)</b>	61 - 200 t
<b>Weight JUWathan® (kg)</b>	385
<b>Dimensions steerable (mm)</b>	670 x 1 275
<b>Supporting surface of turntable Ø (mm)</b>	250
<b>Height (mm)</b>	230
<b>Castor dimensions (Ø x l mm)</b>	200 x 85
<b>Number of castors (Pieces)</b>	20
<b>Load capacity (t)</b>	40

## More images

