

Steerable trolley JL 80 H Professional - NEW

Power and stability - the JLB 40 H transport trolley from JUNG can lift loads of up to 40 t with an installation height of 230 mm.

Product number 09 801 206-H

Weight 617kg



Product description

Features of the JUNG Transport trolleys JL 80 H Professional

- Despite their high load capacity, the transport trolleys feature a compact and weight-optimized design.
- The newly developed steering unit with a reduced number of rollers enables a more compact construction without compromising load capacity – made possible by the use of advanced roller technology.
- The reduced number and optimized arrangement of rollers result in significant weight savings.
- The combination of halved roller width and doubled roller quantity significantly improves maneuverability and greatly reduces frictional forces during cornering.
- A mechanical pendulum suspension of the cassettes or axles ensures even load distribution across all rollers and the ground surface, eliminating the need for a hydraulic leveling system.
- The tank rollers are delivered fully pre-assembled and are ready for immediate use without additional installation effort.
- The steering unit comes standard with a ball-bearing turntable and a tow bar equipped with an integrated towing eye.

JUNG transport trolleys are fitted with ball-bearing rollers for smooth and effortless movement. The rollers come standard with a low-wear tread.

Product properties

Handlebar with pulling eye (mm)	1 600
Load capacity (suitable)	61 - 200 t
Weight JUWAthan® (kg)	617
Dimensions steerable (mm)	820 x 1 480
Supporting surface of turnable Ø (mm)	250
Number of castors (Pieces)	24
Height (mm)	240
Castor dimensions (Ø x l mm)	200 x 85
Load capacity (t)	80

240

Side view of the JLB 80 H roller, showing the two large rollers and the side housing. A dimension line indicates a height of 240 mm.