

# Revolving transport trolley JKB 2 K with locking mechanism

Agile and powerful revolving transport trolley with JUWAmid castors from JUNG. The JKB 2 K transport trolley transports loads up to 2 t with an installation height of 110 mm and locking mechanism.

**Product number** 14 021 085-P

**Weight** 20kg



## Product description

Advantages of the revolving transport trolley JKB 2 K with locking mechanism and JUWAmid

- Optional connecting bars can be fixed without tools by clamping down on adapter.
- With locking mechanism: for fixing the castors in place so that the track is maintained even on uneven floors or when changing direction. The directional lock can be secured or released under load. Can be used for electrically powered chassis as a trailer or steering wheel, as the castors run true to track.
- Despite its low weight, the wheel assembly can transport heavy loads.
- The wheel assemblies are equipped with ball bearing swivel casters that allow for a 360-degree rotation. The narrow width of the casters on all rotary wheel assemblies minimizes the steering and turning resistance, enabling easy movement of the rotation wheel assemblies.
- Mix and match revolving trolleys with transport trolleys: With an installation height of only 110 mm\*, the rotating transport trolley JKB 2 is compatible with all steering and transport undercarriages of the K series.
- All products are also available in a set of two with price advantage.
- Unrivalled: The double roller system reduces rolling and turning resistance to a minimum.
- All wheel assemblies have central drillings to secure the transported goods.
- For choosing the adequate revolving trolley we recommend a load of two-third of the maximum capacity. This will be the most advantageous compromise between payload, ergonomics and handling of the devices.
- Pulling handle and connecting bars available as accessories.

The rotary castors are equipped with JUWAmid wheels made of high-quality polyamide and each containing two ball bearings. These wheels are particularly suitable for flat and smooth industrial floors that have no significant contamination.

\*) Due to technical changes, there may be tolerances of up to + 4.5 mm in the installation height since 2014.

## Product properties

<b>Cassette dimensions (mm)</b>	548 x 495
<b>Castor dimensions (Ø x l mm)</b>	85 x 43
<b>Height (mm)</b>	110
<b>Load capacity (t)</b>	2
<b>Consist of</b>	1 x JKB 2 K
<b>Weight JUWAmid (kg)</b>	20
<b>Number of castors (Pieces)</b>	6
<b>Supporting surface per cassette (mm)</b>	150

More images

