

# Revolving transport trolley JKB 4 K with locking mechanism

Agile and powerful revolving transport trolley from JUNG. The JKB 4 K transport trolley transports loads up to 4 t with an installation height of 110 mm.

**Product number** 14 042 085-P

**Weight** 38kg



## Product description

Advantages of the revolving transport trolley JKB 4 K with JUWAmit castors

- Optional connecting bars can be fixed without tools by clamping down on adapter.
- With locking mechanism: for fixing the castors in place so that the track is maintained even on uneven floors or when changing direction. The directional lock can be secured or released under load. Can be used for electrically powered chassis as a trailer or steering wheel, as the castors run true to track.
- High load capacity at low weight.
- The wheel assemblies are equipped with ball bearing swivel casters that allow for a 360-degree rotation.
- Mix and match revolving trolleys with transport trolleys: With an installation height of only 110 mm\*, the rotating transport trolley JKB 4 is compatible with all steering and transport undercarriages of the K series.
- All products are also available in a set of two with price advantage.
- Unrivalled: The double roller system reduces rolling and turning resistance to a minimum.
- Using the slots in the platform, the rotational trolleys JKB 4 - 8 can be affixed to the load with standard tiedown belts.
- In addition, all the trolleys have a platform center hole to allow attachment to the load.
- For choosing the adequate revolving trolley we recommend a load of two-third of the maximum capacity. This will be the most advantageous compromise between payload, ergonomics and handling of the devices.
- Drawbars and connecting rods are available as accessories in various lengths.
- Inspected according to technical regulation ANSI ? ASME (USA)

It is recommended to select a payload of approximately 2/3 of the maximum load capacity to achieve the best compromise between payload, ergonomics, and handling of the equipment.

\* ) Due to technical changes, there may be tolerances of up to + 4.5 mm in the installation height since 2014.

## Product properties

|                                      |             |
|--------------------------------------|-------------|
| Cassette dimensions (mm)             | 690 x 475   |
| Weight JUWAmid (kg)                  | 37          |
| Supporting surface per cassette (mm) | 250         |
| Castor dimensions (Ø x l mm)         | 85 x 43     |
| Consist of                           | 1 x JKB 4 K |
| Number of castors (Pieces)           | 12          |
| Height (mm)                          | 110         |
| Load capacity (t)                    | 4           |

## More images

