

# Tandem trolley JTLB 6 K

For transporting loads without a center point support - the tandem trolleys JTLB 6 K for loads up to 6 t.

**Product number** 12 061 085-D

**Weight** 46kg



## Product description

Advantages of the tandem trolleys JTLB 6 K

- Tandem transport trolley for loads with no leading or trailing edge center support.
- The double castors design results in dramatically easier steering due to reduced friction forces in curves. The much lower friction resistance also causes the castors on the rear axis to following in directional stability.
- Ready for use: 2 interconnected steerable trolleys with 2 handlebars and two tandem connecting bars.
- Tandem transport trolley in other lengths available on request.
- Multi-purpose use: Also usable as two single trolleys, each with half of the combined load capacity. No additional accessories needed.

## Product properties

<b>Steerable dimensions (mm)</b>	600 x 280
<b>Castor dimensions (Ø x l mm)</b>	85 x 85
<b>Number of twin castors (pcs.)</b>	8
<b>Load capacity (t)</b>	6
<b>Height (mm)</b>	110
<b>Width of track and connection rod (mm)</b>	1 000
<b>Weight Professional (kg)</b>	46
<b>Adjustable from - to Vmin. - Vmax. (mm)</b>	560 - 960
<b>Total length/width (mm)</b>	760 x 1 240
<b>Supporting surface of turnable Ø (mm)</b>	150
<b>Supporting surface per turnable</b>	150
<b>Adjustable</b>	5 x
<b>Handlebar with pulling eye (mm)</b>	990

### More images



