

Adjustable trolley JFB 9 K

High-performance transport trolley from JUNG. The JFB 9 K trolley transports loads up to 9 t with an installation height of 110 mm.

Product number 08 091 085-V

Weight 31kg



Product description

Qualities of the transport trolleys JLB 9 K


- Equipped with highest quality castors as standard.
- Reduced weight due to advanced construction of load cassettes.
- All transport trolleys are ready for use: The adjustable-width transport trolley consists of two transport units and connecting bar.
- Inspected according to technical regulation ANSI ? ASME (USA)

The transport trolleys have a low installation height of only 110 mm, allowing them to fit under almost any load. The transport trolleys come with ball bearing supported rollers that enable effortless maneuvering and positioning. These rollers are equipped with a standard wear-resistant coating called "JUWathan plus", ensuring a smooth and quiet operation. Optionally, the transport trolleys can be equipped with a handle or towing eye for easier transportation.


Product properties

Castor dimensions (Ø x l mm)	85 x 85
Number of castors (Pieces)	2 x 6
Height (mm)	110
Supporting surface per cassette (mm)	170 x 170
Load capacity (t)	9
Load capacity (suitable)	16 - 20 t
Connecting bar with joint (mm)	1 230
Cassette dimensions (mm)	325 x 390
Cassettes adjustable from - to (mm)	400 - 1 030
Weight JUWathan®plus (kg)	32


More images



JFB 9 K | Art-No. 08 091 085 V | Draufsicht | Top view



JFB 9 K | Art-No. 08 091 085 V | Frontansicht | Front view



JFB 9 K | Art-No. 08 091 085 V | Seitenansicht | Side view

